

Technical data

Core	MDF 18mm
Surfaces	Lacquered veneer
Gloss grade	10% +/- 3%
Veneer thickness	0,6mm
Final thickness	19mm
Size	3050x1240mm
Splicing	Mismatch

DESCRIPTION	NORM	RESULT
Density	EN622-5 / EN323	730 kg/m ³ +/- 7%
Internal bond	EN139862004+A12015	0,65 N/mm ²
Bending strength	EN622-5	25 N/mm ²
Modulus of elasticity	EN622-5	2800 N/mm ²
Thickness tolerance	EN324	+/- 0,2mm
Swelling in thickness	EN139862004+A12015	12%
Length/width tolerance	EN324	+/- 2mm/m
Squareness tolerance	EN324	+/- 2mm/m
Flatness	EN324	2mm/m
Formaldehyde	EN139862004+A12015	MDF TSCA Title VI/E0,5
PCP content	EN139862004+A12015	<=5 ppm
Fire classification	EN139862004+A12015	D-s2, d0

* The information in this document has been reliably sourced and compiled with the utmost care and attention to detail. The information and data contained herein is believed to be accurate and correct at the time of printing. We apologize in advance for any misprints, errors or mistakes if they have occurred. LosánNL (we) offers no warranty of any kind, expressed or implied, concerning the accuracy or completeness of the information provided. We will not be liable for claims relating to any party's use of or reliance on the information and data provided, regardless of whether it is claimed that the information is inaccurate, incomplete or otherwise misleading. It is for you to consider, investigate and verify to decide on fitness for purpose. It is the user's responsibility to be aware of any possible changes to technical data and up to date product information that may effect suitability for purpose.