

**DECLARATION OF PERFORMANCE
MEDITE TRICOYA EXTREME (MTX)**

Reference Number: **CADOP09**

MEDITE EUROPE DAC

Redmondstown

Clonmel

County Tipperary

Ireland

Product Type	Intended Use	AVCP*	Approved Body Reference
MDF.H-2	External and internal use as non-structural components	4	Not Applicable
*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011			

Declared Performance

Essential characteristics	Performance					Designated Standard
	4 to <9	9 to <12	12 to <15	15 to <18	18	
Thickness Range						EN 13986:2004+A1:2015
Internal bond (N/mm ²)	0.80	0.80	0.80	0.80	0.80	
Internal bond after boil test (N/mm ²)	0.65	0.65	0.65	0.65	0.65	
Swelling in thickness (24hrs) %	2.5	2.0	2.0	1.5	1.5	
Release of formaldehyde	E1	E1	E1	E1	E1	
Reaction to fire	NPD	E-s2,d0	E-s2,d0	E-s2,d0	E-s2,d0	
Water vapour permeability μ	NPD	NPD	NPD	NPD	NPD	
Airborne sound insulation (surface mass) (R)	NPD	NPD	NPD	NPD	NPD	
Thermal resistance R Value m ² K / W	0.056	0.085	0.114	0.150	0.180	
Biological durability	Use Classes 1,2,3 & 4					
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:



Tom Prendergast, Technical Manager.

Clonmel, Ireland. 12/07/2021