

DECLARATION OF PERFORMANCE MEDITE CLEAR

Reference Number: CADOP08

MEDITE EUROPE DAC

Redmondstown

Clonmel

County Tipperary

Ireland

Intended Use	AVCP*	Approved Body Reference
Internal use as non- structural components in dry conditions	4	Not Applicable
	Internal use as non- structural components in dry	Internal use as non- structural components in dry

Declared Performance

Essential characteristics		Performance	9	Designated Standard
Thickness Range	6 to <9	9 to 12	>12 to 19	
Internal bond (N/mm²)	0.65	0.60	0.55	
Swelling in thickness %	17	15	12	
Release of formaldehyde	E1	E1	E1	m
Reaction to fire	NPD	D-s2,d0	D-s2,d0	EN 13
Water vapour permeability µ	NPD	NPD	NPD	13986:2004+A1:2015
Airborne sound insulation (surface mass) (R)	NPD	NPD	NPD	004+
Sound absorption Frequency range 250Hz to 500Hz (α)	NPD	NPD	NPD	A1:2
Sound absorption Frequency range 1000Hz to 2000Hz (α)	NPD	NPD	NPD	015
Thermal conductivity λ	NPD	NPD	NPD	
Biological durability	Use Class 1	<u> </u>		
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:

Tom Prendergast, Technical Manager.

Clonmel, Ireland. 08/07/2021